

3590EXT

3590EXT "ENTERPRISE": WEIGHT INDICATOR FOR INDUSTRIAL APPLICATIONS, in STAINLESS STEEL IP68



High performance digital weight indicator, with 3 serial ports, transmission protocols for data communication, completely configurable printouts, integrated alibi memory and port for connection to barcode/badge reader. The wide range of connectable accessories and printers guarantees the maximum interfaceability and versatility. CE-M approvable (OIML R-76 / EN 45501).



The best solution
for advanced industrial
applications

MAIN FEATURES

- 25-key alphanumeric waterproof keyboard.
- Highly efficient red led display with 6 digits 15mm high.
- Backlit LCD graphic 25x100mm display.
- Synoptic bar graph with 16 bright LEDs showing the active functions.
- Easy to clean STAINLESS STEEL waterproof IP68 enclosure; resistant to harsh and corrosive environments.
- Dimensions: 264x115x174 mm.
- Suitable for use on the table, column, or wall.
- Real time clock and permanent data storage.
- Fitted alibi memory, integrated on the motherboard.
- Functions available with DINITOOLS utility
 - Configuration, calibration, data entry and print formatting.
 - Recording and filing of all the information on PC.
 - Complete retrieval of the data saved for quick substitution.
 - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- 4 independent analogue channels (up to 2 in the E-AF03 version, 1 in the E-AF09 version) for reading of the weight.
- Management of 16 analog load cells of 350 Ohm (45 cells at 1000 Ohm);
NOTE: for the management of digital load cells for weigh bridges, see the range of [touchscreen indicators](#).
- Up to 10.000e OIML or 3 x 3000e @ 0,3 μ V/e CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Connectable to printers and labellers with the command drivers.
- 110-240 Vac power supply; built-in rechargeable battery for use in prolonged absence of the power mains (incompatible with IOEXPB board).

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 - MID
- OIML R134 (AF09)
- Australian legal for trade certificate of approval (NMI S788)

APPLICATION SOFTWARE

- SUPPLIED AS STANDARD:
- AF01: Totalization and formula weighing

OPTIONAL:

- AF02: Pieces/quantity counting
- AF03: Weighbridges - Input/Output vehicle
- AF04: Statistical checking of prepackaged goods
- AF05: Price computing and industrial labelling
- AF08: Wheel and axle static weighing with 2 or various platforms
- AF09: Dynamic and static axle weighing with 2 platforms
- BATCH1: Single product dosage systems in loading and unloading
- BATCH: Multicomponent dosage systems in loading and unloading
- CHECK: Weight packages on a conveyor belt functions
- BELT: Reading/regulation function of the flow on the weighing belt
- LW: Continuous dosage in unloading

CUSTOMISED APPLICATIONS

Thanks to our integrated development, you can create complete customised applications in autonomy:

- wizards, operator messages
- serial port management, protocols customization
- digital I/O full management
- sequential or simultaneous automations
- data entry, custom archives

Dini Argeo can offer the service of custom development programs.

I/O SECTION

- 2 RS232 serial ports, for connection to printer, PC or PLC, radio module, and optional interfaces.
- 1 RS232 serial port (optional RS485), for connection to repeater, remote scale, badge reader.
- Fitted keyboard emulation input, for barcode/badge readers or external PC keyboard, through cable with mini DIN connector (optional).
- 4 (16 in the IO versions) optoisolated outputs (optional).
- 2 (8 in the IO versions) optoisolated inputs (optional).
- External Profibus interface (optional), for automation management (depending on the software program).
- Modbus RTU Protocol.
- Optional Bluetooth connection, for quick wireless programming of the activities and the formulas, through PC, tablet or smartphone.

DETAIL 1



3590EXT with IP65 optional printer



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE