

JB4AI

"JBAI": SCATOLA DI GIUNZIONE PER AMBIENTI ATEX, FINO A 4 CELLE DI CARICO



Scatola di giunzione in acciaio inox con grado di protezione IP66 da acqua e polveri, per unione di 1, 2, 3 o 4 celle. Marcatura:
ATEX II 2G Ex ib IIC T6 Gb per gas.
ATEX II 2D Ex tb IIIC T115°C Db IP65 per polveri.

La soluzione ideale per
applicazioni industriali
avanzate

CARATTERISTICHE TECNICHE

- Progettate e realizzate in accordo con la direttiva ATEX, gruppo II categoria 2GD, secondo le norme IEC/EN60079-0, IEC/EN60079-11 e IEC/EN60079-31.
- Involucro in acciaio inox.
- Pressacavi metallici PG9.
- Grado di protezione: IP66.
- Dimensioni: 190x130x45mm (lxwxh).

NOTA: dimensioni non compatibili per montaggio su piattaforme/pesa pallet a 4 celle.



“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE