

WIFITD

"WIFITD": INTERFACCIA WI-FI PER INDICATORI DI PESO



Modulo wifi di dimensioni ridotte per montaggio e collegamento interno all'indicatore tramite il cavo in dotazione. L'antenna adesiva applicabile alla scocca dell'indicatore permette il collegamento di qualsiasi bilancia o sistema di pesatura al sistema informatico aziendale.

La soluzione ideale per
applicazioni industriali
avanzate

CARATTERISTICHE TECNICHE

- Configurazione tramite WIFI/ethernet.
- Dispositivo standard WiFi IEEE 802.11b/g/n.
- Dimensioni: Altezza 17 mm; Larghezza 50 mm; Lunghezza 89 mm.
- Portata: 70m outdoor, 25m indoor. Questa distanza può subire variazioni a seconda del materiale del case dello strumento utilizzato e dell'ambiente di installazione.
- Frequenza: 2.4/2.5 GHz.
- Data Rate: fino a 500Kbps.
- Protocolli e modi di funzionamento: IEEE 802.11b/g/n, WEP, WPA e WPA2-PSK(AES/TKIP).
- Temperatura di stoccaggio: -40°C +95°C.
- Alimentazione: 5Vdc

N.B. ACCESSORIO ORDINABILE SOLO IN ABBINAMENTO CON INDICATORE DI PESO IDONEO



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE