

OBCLT

"OBCLT": SEMAFORO PER CONTROLLO TOLLERANZA CON AVVISO ACUSTICO



Option Box con semaforo a 3 vie con segnale acustico programmabile, bar graph controller, solidale a indicatore della serie DFW e 3590. Il box semaforo consente la gestione di 3 ZONE LUMINOSE e del BUZZER, in modo indipendente, sfruttando la logica TTL.

La soluzione ideale per
applicazioni industriali
avanzate

CARATTERISTICHE PRINCIPALI

- Segnalazione luminosa con 3 gruppi di 15 Led ciascuno
- Segnalazione acustica tramite buzzer
- Alimentazione: da 5,5 a 7,5 Vdc
- Corrente assorbita:

Massima: 320 mA (tutte le zone accese + buzzer)

Tipica: 140 mA (una sola zona accesa)

N.B. ACCESSORIO ORDINABILE SOLO IN ABBINAMENTO CON INDICATORE DI PESO IDONEO



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE